

# PC-2111

Specification	PC-2111
Processor	Intel Apollo Lake N3350; Intel Apollo Lake J3455
System Memory	DDR3L SO-DIMM x 2, max. 8GB in 2 slots
Storage Device	M.2 connector [SATA Signal Only] x 1
Power Supply	12V/40W
OS Support	Windows 10 IoT 64 bit
<b>Display &amp; Touch</b>	
LCD	10.1" TFT LCD
Resolution	1280 x 800
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)
<b>I/O &amp; Expansion</b>	
Serial Port	N/A [ RJ45 x 1 can be supported as Non-Standard Order]
Standard USB Port	USB 2.0 x 2
LAN Port	10/100/1000 Mb x 1
Display Port	N/A [ VGA x 1 can be supported as Non-Standard Order]
Audio	N/A [2W speaker x 1 can be supported as Non-Standard Order]
Expansion Slot	M.2 x 1 for WiFi/BT module
<b>Physical Dimension</b>	
Dimension [W x D x H in mm]	285 x 37 x 173
Weight [N. W. in kg]	-
<b>Environmental</b>	
Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH
<b>Attachment Options</b>	
Attachment	Side attachment with external USB 2.0 port

# POSIFLEX

## Extraordinary Within



# PC-2111

## 10.1" Panel PC

\*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.  
\*The product information and specifications are subject to change without prior notice.  
\*Please refer to the website for more attachment options.

Certifications



EN202102V1

# POSIFLEX

**POSIFLEX TECHNOLOGY, INC.**

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan  
Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw  
Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller